

LED line PRIME

Symbol: 470218-II

EAN: 5905378201545

**LED BULB GU10 10W 2700K 1250lm
DIMMABLE**



Dane techniczne

Parametr	Wartość
Luminous efficacy	125
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	1250
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	5
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	30 000 h
Material	Ceramic
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Lamp's type	GU10

Parametr	Wartość
Lamp's diameter	50 mm
Beam angle	120
Material (housing)	Ceramics
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,7
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100
Lamp's warm-up time to 60%	1 s
Height	55
Power	• 10 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 2700 K

LED line PRIME

Symbol: 470218-II

EAN: 5905378201545


**LED BULB GU10 10W 2700K 1250lm
DIMMABLE**

Wymiary

Rozsył światła


Dodatkowe zdjęcia produktowe

Dane logistyczne




Opakowanie jednostkowe

Width	50 mm
Height	63 mm
Length	50 mm
Weight	0,06 kg
	1



Opakowanie zbiorcze

Number of pieces/tape in meters pack zb	100 szt.
Width	575 mm
Height of collective packaging	155 mm
Length	280 mm
Weight	7
Volume	0,024 m ³



Europaleta

Quantity collective euro pallet	4800 szt.
Weight of a euro pallet	336 kg
Pallet height	1860 mm
Quantity in 1 layer	400 szt.
Number of layers	12

LED line PRIME

Symbol: 470218-II

EAN: 5905378201545

**LED BULB GU10 10W 2700K 1250lm
DIMMABLE**

Przykładowa realizacja